Parktron 博 辰 科 技

C4

び 智慧零售 Smart Retail





自助點餐機 Self-Payment Kiosk for Retail http://www.parktron.com

Features

- Enhanced efficiency & profit : through the highly integration with existing POS system, to enhance the processing from order, serve to payment, in order to increase the income but less labor cost.
- Multiple payment : support cash, credit card, prepaid card, mobile payment ... through the integration with local payment gateway.
- Advanced cash validator technology : work with worldwide leading technology supplier to make sure each transaction in the highest security level.
- Intuition interface : interactive & user-friendly interface design.
- Playing advertisement
- Useful report system : from the daily report database, to provide the useful information of sales performance by timeline and category.
- Seamless integration : easy to integrate with existing POS system.

Specification

- IPC Industrial low power half-size Pentium CPU board.
- Isolated digital I/O card.
- 21.5" color TFT-LCD touch display.
- Thermal printer for payment receipt.
- Multimedia speaker.
- Sub-intercom device.
- Banknote Accepter/Collector :
 - Multi-width and four-way validation.

- Single-Stacking Cassette with security lock (Capacity: 1000 notes).

- Coin Accepter :
 - Automatic safety shutter only opens when awaiting for payment.
 - Accept multiple coin types in one single slot.
- Coin Hopper :
 - Standard 3 (max. 4) coin hoppers for different denomination storage & providing 3 (max. 4) coin change.
 - A storage size of 500~1000 coins per hopper depends on coin size.
- Cabinet :
 - 3.0mm thickness heavy duty hot-rolled steel for front door panel and 2.0mm for entire cabinet.
 - Polyester powder coating.
 - Ventilation system.
 - Internal service illumination.
- Alarm monitoring and control :
 - Real time alarm monitoring and alert to the Central Management Server.
 - Alarm types: cabinet intrusion/collision, coin/banknote full, coin low, device/communication errors ...etc.
 - Blacklist alert to Central Management Server.
 - Alarm buzzer for illegal intrusion.
- Working Temperature : -10 ~ 50°C.
- Electrical : 100/220VAC, 50/60Hz.
- Dimensions (W x D x H) : 620 x 350 x 840mm (±3%).